Amendments to and Listing of the Claims:

Claims 1 to 12 (Cancelled)

13. (Currently Amended) A gasoline additive for a direct injection gasoline engine which comprises a nitrogen-containing compound represented by the formula:

wherein R¹ is hydrogen, R², R³, R⁴ and R⁵ are each independently selected from the group consisting of hydrogen, a C₁ - C₁₆ hydrocarbon group and a group of the formula (2a) below, a is an integer from 1 to 200 an integer from 26 to 30 and X is a group selected from Group B below,

said formula (2a) being

wherein R^7 and R^8 are each independently selected from the group consisting of hydrogen, a C_1 - C_{10} hydrocarbon group and a C_2 - C_{10} alkoxyalkyl group, R^9 is a C_2 - C_6 alkylene group or a C_4 - C_{10} alkylene group having an alkoxyalkyl substituent, R^{10} is hydrogen or a C_1 - C_{30} hydrocarbon group, and f is an integer from 0 to 50;

said Group B being constituted by

- (B1) hydrogen,
- (B2) a C₁ C₃₀ hydrocarbon group,
- (B3) an alkanol group represented by the formula

$$-R^{14}$$
- OH (3a)

wherein R^{14} is a $C_1 - C_6$ alkylene group,

i (Re-Submitted) (B4) a nitrogen-containing group represented by the formula

$$R^{15} \xrightarrow{N} R^{17}$$

$$R^{16} \xrightarrow{g} 4a$$

wherein R^{15} is a C_2 - C_6 alkylene group, R^{16} is selected from the group consisting of hydrogen, a C_1 - C_4 alkyl group, and a group of the formula (3a), R^{17} is selected from the group consisting of hydrogen, a C_1 - C_{30} hydrocarbon group and a group of the formula (3a), and g is an integer from 1 to 5, and

(B5) a group represented by the formula

wherein R^{18} is a $C_2 - C_6$ alkylene group, R^{19} , R^{20} , R^{21} , and R^{22} are each independently selected from the group consisting of hydrogen, a $C_1 - C_{10}$ hydrocarbon group and a hydroxyl group, Y is selected from the group consisting of a methylene group and a methylene group substituted by either a $C_1 - C_{10}$ hydrocarbon group, a hydroxyl group, an imino group, an imino group substituted by a $C_1 - C_{10}$ hydrocarbon group or a hydroxyl group, or oxygen, and h is equal to 0 or 1.

15. (Previously Presented) The gasoline additive according to claim 13, wherein R^2 , R^3 , R^4 , and R^5 are each independently selected from the group consisting of hydrogen, a C_1 - C_{12} straight or branched alkyl group and a group represented by formula (2a) wherein R^7 and R^8 are each independently hydrogen or a C_1 – C_3 alkyl group, R^{10} is a C_1 – C_{12} alkyl group, and f is equal to 0.

- 16. (Previously Presented) The gasoline additive according to claim 13, wherein X is (B1) or (B3) and wherein (B3) is a group represented by formula (3a) in which R^{14} is a C_2 C_3 alkylene group.
- 17. (Currently Amended) A gasoline composition for use in a direct injection gasoline engine, which composition comprises gasoline and a nitrogen-containing compound represented by the formula:

wherein R^1 is hydrogen, R^2 , R^3 , R^4 and R^5 are each independently selected from the group consisting of hydrogen, a C_1 - C_{16} hydrocarbon group and a group of the formula (2a) below, a is an integer from 1 to 200 an integer from 26 to 30 and X is a group selected from Group B below,

said formula (2a) being

wherein R^7 and R^8 are each independently selected from the group consisting of hydrogen, a C_1 - C_{10} hydrocarbon group and a C_2 - C_{10} alkoxyalkyl group, R^9 is a C_2 - C_6 alkylene group or a C_4 - C_{10} alkylene group having an alkoxyalkyl substituent, R^{10} is hydrogen or a C_1 - C_{30} hydrocarbon group, and f is an integer from 0 to 50;

said Group B being constituted by

- (B1) hydrogen,
- (B2) a C₁ C₃₀ hydrocarbon group,
- (B3) an alkanol group represented by the formula

$$-R^{14}$$
- OH (3a)

wherein R^{14} is a $C_1 - C_6$ alkylene group,

(B4) a nitrogen-containing group represented by the formula

$$R^{15} \xrightarrow{N} R^{17}$$

$$R^{16} \xrightarrow{g} 4a$$

wherein R^{15} is a C_2 - C_6 alkylene group, R^{16} is selected from the group consisting of hydrogen, a C_1 - C_4 alkyl group, and a group of the formula (3a), R^{17} is selected from the group consisting of hydrogen, a C_1 - C_{30} hydrocarbon group and a group of the formula (3a), and g is an integer from 1 to 5, and

(B5) a group represented by the formula

$$R^{19}$$
 R^{20}
 R^{20}
 R^{21}
 R^{22}
 R^{22}
 R^{22}

wherein R^{18} is a $C_2 - C_6$ alkylene group, R^{19} , R^{20} , R^{21} , and R^{22} are each independently selected from the group consisting of hydrogen, a $C_1 - C_{10}$ hydrocarbon group and a hydroxyl group, Y is selected from the group consisting of a methylene group and a methylene group substituted by either a $C_1 - C_{10}$ hydrocarbon group, a hydroxyl group, an imino group, an imino group substituted by a $C_1 - C_{10}$ hydrocarbon group or a hydroxy group, or oxygen, and h is equal to 0 or 1.

18. (Previously Presented) The gasoline composition according to claim 17, wherein the nitrogen-containing compound is contained in an amount of 0.001 to 10 mass percent, based on the total composition.

iv (Re-Submitted)

19. (Cancelled)

- 20. (Previously Presented) The gasoline composition according to claim 17, wherein R^2 , R^3 , R^4 , and R^5 are each independently selected from the group consisting of hydrogen, a C_1 - C_{12} straight or branched alkyl group and a group represented by formula (2a) wherein R^7 and R^8 are each independently hydrogen or a $C_1 C_3$ alkyl group, R^{10} is a $C_1 C_{12}$ alkyl group, and f is equal to 0.
- 21. (Previously Presented) The gasoline composition according to claim 17, wherein X is (B1) or (B3) and wherein (B3) is a group represented by formula (3a) in which R^{14} is a C_2 - C_3 alkylene group.
 - 22. (Cancelled)
 - 23. (Cancelled)
- 24. (Currently Amended) A method for controlling deposits formed in a combustion chamber of a direct injection gasoline engine, the method comprising using a gasoline composition which comprises gasoline and a nitrogen-containing compound represented by the formula

$$\begin{array}{c|c}
R^2 & R^3 \\
\hline
O & C & C \\
\hline
R^4 & R^5
\end{array}$$
O — CH_2CH_2 —N-(X)₂

wherein R¹ is hydrogen, R², R³, R⁴ and R⁵ are each independently selected from the group consisting of hydrogen, a C₁ - C₁₆ hydrocarbon group and a group of the formula (2a) below, a is an integer from 1 to 200 an integer from 26 to 30 and X is a group selected from Group B below,

said formula (2a) being

wherein R^7 and R^8 are each independently selected from the group consisting of hydrogen, a C_1 - C_{10} hydrocarbon group and a C_2 - C_{10} alkoxyalkyl group, R^9 is a C_2 - C_6 alkylene group or a C_4 - C_{10} alkylene group having an alkoxyalkyl substituent, R^{10} is hydrogen or a C_1 - C_{30} hydrocarbon group, and f is an integer from 0 to 50;

said Group B being constituted by

- (B1) hydrogen,
- (B2) a C₁ C₃₀ hydrocarbon group,
- (B3) an alkanol group represented by the formula

$$-R^{14}$$
- OH (3a)

wherein R^{14} is a $C_1 - C_6$ alkylene group,

(B4) a nitrogen-containing group represented by the formula

$$R^{15} \xrightarrow{N} R^{17}$$

$$R^{16} \xrightarrow{g} 4a$$

wherein R^{15} is a C_2 - C_6 alkylene group, R^{16} is selected from the group consisting of hydrogen, a C_1 - C_4 alkyl group, and a group of the formula (3a), R^{17} is selected from the group consisting of hydrogen, a C_1 - C_{30} hydrocarbon group and a group of the formula (3a), and g is an integer from 1 to 5, and

(B5) a group represented by the formula

$$\begin{array}{c|c}
R^{19} & R^{20} \\
\hline
 & R^{21} & R^{22} & 5a
\end{array}$$

vi (Re-Submitted) wherein R^{18} is a $C_2 - C_6$ alkylene group, R^{19} , R^{20} , R^{21} , and R^{22} are each independently selected from the group consisting of hydrogen, a $C_1 - C_{10}$ hydrocarbon group and a hydroxyl group, Y is selected from the group consisting of a methylene group and a methylene group substituted by either a $C_1 - C_{10}$ hydrocarbon group, a hydroxyl group, an imino group, an imino group substituted by a $C_1 - C_{10}$ hydrocarbon group or a hydroxy group, or oxygen, and h is equal to 0 or 1.

- 25. (Previously Presented) The method according to claim 24, wherein the nitrogen-containing compound is contained in the gasoline composition in an amount of 0.001 to 10 mass percent, based on a total mass of the composition.
- 26. (Previously Presented) The method according to claim 24, wherein R^2 , R^3 , R^4 , and R^5 are each independently selected from the group consisting of hydrogen, a $C_1 C_{12}$ straight or branched alkyl group and a group represented by formula (2a) wherein R^7 and R^8 are each independently hydrogen or a C_1 C_3 alkyl group, R^{10} is a $C_1 C_{12}$ alkyl group, and f is equal to 0.
- 27. (Previously Presented) The method according to claim 24, wherein X is (B1) or (B3) and wherein (B3) is a group represented by formula (3a) in which R^{14} is a $C_2 C_3$ alkylene group.
 - 28. (Cancelled)